









AP Revision number: 2 Date: 07-2017

ICS Performance Guarantee

The ICS Performance Guarantee combines our films with qualified components to form a system which is guaranteed to be compatible and provide outstanding performance. Granted to all customers working according to the relevant Avery Dennison Instructional Bulletins, the ICS Performance Guarantee offers a range of choice and flexibility. You choose the application and couple it with our films – and we provide the warranty.

Please refer to Avery Dennison ICS Performance Guarantee Terms and Conditions 1.0 for further details.

Avery Dennsion Wrapping Films	period p in years ir		Warranted period in years Zone 2		Warranted period in years Zone 3		Application Substrate				
Supreme Wrapping Film	Outdoor Vertical	Outdoor Horizontal	Outdoor Vertical	Outdoor Horizontal	Outdoor Vertical	Outdoor Horizontal	Flat	Simple curves	Rivets	Compound curves	Deep Recesses & Corrugations
- Opaque Colours (Gloss, Satin & Matte)	10	2	7	1.5	4	1	•	•	•	•	•
- Extreme Texture (including Carbon and Brushed)	5	2	3.5	1.5	2	1	•	•	•	•	-
- Metallics (Gloss & Matte)	5	2	3.5	1	2	0.5	•	•	•	•	•
- Pearlescents	5	2	3.5	1	2	0.5	•	•	•	•	•
- ColorFlow Series	5	2	3.5	1	2	0.5	•	•	•	•	•
- Diamond (Ultrametallics)	5	2	3.5	1	2	0.5	•	•	•	•	•
- Conform Chrome (including Colours and with Transparent COL's applied)	3	1.5	2	1	1	0.5	•	•	•	•	-

Important Note: Where the material is applied in a 'marine environment', the stated warranty period will be reduced by 40%.













Avery Dennison® ICS Performance Guarantee Additional information on graphics durability

Expected Durability and Potential Durability Reductions


The expected durability of Avery Dennison films are defined as the expected performance life of the Avery Dennison graphic film(s) within the Asia Pacific region in outdoor vertical exposure conditions.


The actual performance life will depend on a variety of factors, including selection and preparation of substrate, angle and direction of exposure, application methods, environmental conditions and cleaning/maintenance of the films. In case of films used in areas of high temperatures or humidity, high altitudes and industrially polluted areas the performance will be further reduced. Where the material is applied in a 'marine environment', the stated warranty period will be reduced by 40%.


Expected Durability and Warranted Period Definitions

Expected durability is the expected period of time defined in the product data sheet, the product should, but is not warranted to, perform satisfactorily when applied in vertical exposure conditions as defined in Instructional Bulletin 1.30. The warranted period communicated in this ICS Performance Guarantee Bulletin, is the maximum period of time Avery Dennison will warrant the finished products performance in accordance with ICS Performance Guarantee Terms and Conditions 1.0, provided that the film is properly stored, converted and installed and maintained in accordance with Avery Dennison guidelines.

Angle and Direction of Exposure







vertical, for Supreme Wrapping Film (SW900) Horizontal applications will be warranted as stated in the relevant ICS performance guarantee

Other Potential Durability Reductions

High elevations: In mountain areas UV damage is increased over exposures at sea level. This is due to the air being thinner and therefore damage of UV radiation increases significantly. Congested urban or industrial areas: Due to increased smog, pollutants and particulates in the atmosphere, applications of this kind have reduced durability expectations. Horizontal applications trap pollutants on the surface of the material, increasing the impact of UV exposure and reducing durability.













Avery Dennison® ICS Performance Guarantee Additional information on graphics durability

Zone System Asia Pacific

Durability for regions located in Zone 2 may be stated in ICS Performance Guarantee Durability Bulletins and other warranty documents issued by Avery Dennison Asia Pacific. Therefore, films used in regions identified as Zone 3 will have a reduction of the stated durability by 40%. If the film is applied whereby a combination of non-vertical and Zone 3 exposure, the cumulative effect of the reduced exposures would apply. Therefore the non-vertical exposure in Zone 3 would be 70% less than the stated durability.

Zone and Non-Vertical Reduction Examples Asia Pacific

Zone 1		Zone 2 (values as	in this ICS Bulletin)	Zone 3			
Vertical	Non-vertical	Vertical	Non-vertical	Vertical	Non-vertical		
100%	-50% of Zone 1 Vertical	-30% Zone 1 Vertical	-50% Zone 2 Vertical	-40% Zone 2 Vertical	-70% of Zone 2 Vertical		
7	3.5	5	2.5	3	1.5		
5	2.5	3.5	1.75	2	1		
4	2	3	1.5	1.75	0.75		
3	1.5	2	1	1	-		

Values in years

Asia Pacific Zone Chart

Zone 1			Zone 2	Zone 3				
Austria *Australia (Tasmania) Belarus Belgium Bosnia & Herzegovia Canada Denmark Ecuador Estonia Finland France* Georgia Germany Hungary Iceland Italy Latvia Liechtenstein Lithuania Luxembourg Macedonia Monaco Netherlands, the Norway Poland Romania Russia Slovakia Slovenia Sweden Switzerland	United Kingdom Ukraine Uzbekistan Vatican City Yugoslavia *except areas noted as Zone 2 or Zone 3	Andorra Australia* Azerbaijan Bangladesh Belize Bhutan Burkina Faso Burundi Cambodia Cameroon Cape Verde Caribbean Isles China Cyprus Dominican Republic East Timor El Salvador Fiji Greece Grenada Guinea Guinea Guyana Haiti Honduras India Indonesia Ivory Coast Jamaica Japan Kazakhstan Korea (South) Kyrgyzstan Laos Lesotho Madagascar	Maldives Malta Mauritania Mauritania Mauritius Micronesia Moldova Myanmar (Birma) Nepal New Zealand Nicaragua Pakistan Papua New Guinea Paraguay Philippines Portugal Puerto Rico Rwanda Samoa San Marino Sao Tome & Principe Singapore South Africa (East) Sri Lanka Suriname Swaziland Taiwan Thailand Togo Trinidad & Tobago Turkey Turkmenistan Ukraine Uruguay Utah Vietnam	Angola Bahrain Botswana Central African Rep. Chad Congo Egypt Equatorial Guinea Eritrea Ethiopia Gabon Gambia Ghana Guinea-Bissau Iraq Israel Jordan Kenya Kuwait Lebanon Liberia Libya Mali Mexico Morocco Mozambique Namibia New Mexico Niger Nigeria Oman Qatar Saudi Arabia	Senegal Sierra Leone Somalia Tanzania Tunisia Uganda United Arab Emirates Yemen Zambia Zimbabwe *Exposed at all sites above altitudes of 1000 meters *Australia – Above a line 100km north of Perth/Brisbane *Australia – Desert areas			
		Malaysia	3					

